



FLR9Y-A/B



APPLICATION

The FLR9Y cable is a reduced wall thickness PP insulated single-core cable is used for cable harnesses, Halogen-free. Heat resistant.

Technical data

Conductor: Soft-annealed electrolytic copper Cu-ETP1 according to DIN EN 13602, bare or tinned. Conductor construction according to ISO 6722.

Insulation: Polypropylene insulation (PP)

Temperature Rating: -40° C to +125° C (3000h)

Voltage rating: 60V d.c, 25V a.c



The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.



Nominal section (mm ²)	Number/strand Diameter (mm)	Nominal Insulation thickness (mm)	Nominal outer diameter (mm)	20 °C Maximum conductor resistance (Ω/km)
FLR9Y-A				
0.22	7/0.21	0.25	1.2	84.8
0.35	7/0.27	0.25	1.3	54.4
0.5	19/0.19	0.28	1.6	37.1
0.75	19/0.24	0.3	1.9	24.7
1	19/0.27	0.3	2.1	18.5
1.5	19/0.33	0.3	2.4	12.7
2.5	37/0.28	0.235	3	7.6
4	37/0.38	0.4	3.7	4.71
6	37/0.45	0.4	4.3	3.14
FLR9Y-B				
0.35	12/0.21	0.25	1.4	54.4
0.5	16/0.21	0.28	1.6	37.1
0.75	24/0.21	0.3	1.9	24.7
1	32/0.21	0.3	2.1	18.5
1.5	30/0.26	0.3	2.4	12.7
2.5	50/0.26	0.35	3	7.6
4	56/0.31	0.4	3.7	4.71
6	84/0.31	0.4	4.3	3.14
10	80/0.41	0.6	6	1.8

Note: We can produce various specifications of products according to customer requirements

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.